
NOTES

The cost of epoxy grouting threaded rods shall be included with Reinforcement Bars, Epoxy Coated.

Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work. Reinforcement bars designated (E) shall be epoxy coated.




SECTION B-B

Hatched areas indicate removal.

* Epoxy grout n(E) bars in 9" min. holes according to Article 584 of the Standard Specifications.






ELEVATION

13'-9"

SECTION A-A

MAY 1, 2012



BILL OF MATERIAL

Bar	No.	Size	Length	Shape
hu2(E)	22	#5	13'-5"	
n(E)	80	#5	2'-5"	<u>د</u>
S13(E)	30	#5	12'-7''	
Concrete Removal			Cu. Yd.	3.8
Concrete Structures			Cu. Yd.	10.2
Reinforcement Bars, Epoxy Coated			Pound	900

EXPIRES 11-30-2012

			L	_8	
DESIGNED	DAB	EXAMINED	loss Food	YtL	DATE -
CHECKED	VP	1	A TING ENGINEER	F STAUTURAL SERVICES	-
DRAWN	baliva	PASSED \		In and	REVISED
CHECKED	DAB VP			BRIDGES AND STRUCTURES	REVISED

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PIER CRASHWALL EXTENSION SN 032-0090 SHEET NO. 18 OF 19 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.		
55	D3 IMPACT ATTENUATOR	GRUNDY	96	27		
	2012-3	CONTRACT NO. 66CO1				
TILINOIS FED. AID PROJECT						